



**(Contour Edge)**

- Permissible Design Wind Speed W33 (33m/sec)
- Overall dimensions represent clearance dimensions for the complete structure.
  - A minimum of 100mm clearance to any buildings, poles etc. is recommended.
  - Dimensions are in millimetres.

**SAMPLE USE ONLY 5M X 10M**

|  |  |
|--|--|
| ANCHOR BOLT LOCATION TOLERANCES. PER AS 4100-1990                    | - 6mm FROM ANCHOR BOLT GROUP CENTRE TO COLUMN LINE CENTRE. |
| - 3mm FOR ANCHOR BOLT CENTRES WITHIN AN ANCHOR BOLT GROUP.           |  |
| - 6mm FOR ADJACENT ANCHOR BOLT GROUP CENTRES.                        |  |
| - MAXIMUM ACCUMULATION OF 6mm PER 30m NOT TO EXCEED A TOTAL OF 25mm. |  |
| TOLERANCES - U.N.O.  |  |
| LESS THAN 50mm   | ±0.5mm   |
| 50mm TO 2000mm   | ±1.0mm   |
| GREATER THAN 2000mm  | ±2.0mm   |
| ALL ANGLES TO BE   | ±0.5°  |

|                      |                     |
|----------------------|---------------------|
| PROJECT:             |                     |
| TITLE:               | <b>FRAMING PLAN</b> |
| A ISSUE FOR APPROVAL | 06.09.05            |
| REVISIONS            |                     |



|                     |          |
|---------------------|----------|
| DRAWN :             | CHECKED: |
| SCALE : 1:100 AT A3 | DATE : D |
| DRG. No. PS50-      | REV      |